Chung Ciu 06-1-6

Public Meeting to Consider an Update on Implementation of ARB/Railroad Statewide Agreement and to take Action as Appropriate

Chung S. Liu, D.Env.

Deputy Executive Officer, Science & Technology Advancement
South Coast Air Quality Management District

Sacramento, California January 27, 2006

UP/BNSF/SWRI Summary of Current DPF Technology for Locomotives

- Address Part 8, Agreement to Evaluate other, Medium and Long-Term Alternatives
- Summarize Experience in Europe
- DPF retrofits on existing high-horsepower locomotive are not investigated in US because no sufficient space and oxycat retrofits will be tested.

- Booz Allen Hamilton "Locomotive Emission Study" for CARB (1990)
- Engine, Fuel, and Emissions
 Engineering "Controlling Locomotive Emissions in California" for CARB (1994)

Recommend Locomotive Retrofit
Devices including **DPF** and **SCR** with
Space Consideration

GasRail USA LaCHIP LNG Technology Development

- · LaCHIP Late-Cycle High-Injection Pressure
- Applies to GM EMD two-cycle engines
- Dual Fuel uses LNG and diesel fuel (20:1)
- Diesel fuel injected to initiate combustion
- High pressure NG injected into combustion
- NOx reduced 75% diesel-like fuel economy and power

GasRail USA – Develop Low-NOx LNG Locomotive


- 1992 GasRail USA starts SwRl contractor sponsors: DOE, EPA, CARB, others
- 1996 LaCHIP selected to develop / demo
- 1997 Bench Test Results show feasibility of achieving 2.8 g/bph
- 1998 CARB-RR sign South Coast NOx MOU
- 1999 EPA adopts locomotive standards
- 1999 GM-EMD withdraws from GasRail
- 2000 GasRail concluded no LaCHIP demo AQMD spent \$1.75M, Others \$6.6M

"California Emission Program (CEP) PM Reduction from EMD Locomotives"


- Set-up test engine laboratory
- Select lube-oil control technologies
 Power assemblies (piston, cyl, rings)
 Crankcase blow-by
 Valve stem seals
- Laboratory engine durability testing of 3 selected technologies
- Locomotive demonstration


"California Emission Program (CEP) PM Reduction from EMD Locomotives"

2000 CARB-RR agreement - RRs to spend
\$5M to reduce PM from EMD switchers
2001 SwRI starts CEP - contracts with AAR
2004 Lube oil studies completed
2005 Three control technologies selected
2 Diesel Oxidation Cats, 1 DPF
12-31-05 MOU deadline, only \$1.5M spent









Filtration Efficiency	New State	After 2000 Hours
Particle Count 20-300 nm	> 95%	> 95%
EC Mass Concentration	> 90%	> 90%

General Electric – Proposed "Retrofittable DPF for Main Line Locomotives"

- Develop DPF for 4500-HP locomotives
- · Use fibrous ceramic media
- · Use diesel fuel injector aid regeneration
- 90% filtration, only 1% fuel penalty
- Retrofittable to UP and BNSF locomotives

GE Proposed DPF Retrofit for Main Line Locomotives

- Current DPF Systems
 - Extruded ceramic monoliths wall-type filter
 - Regeneration by a separate diesel fuel injector
- GE Proposed DPF System
 - Fibrous ceramic media type filter using the principal of depth filtration
 - Regeneration by system integration and control techniques
- Reduce the <u>size</u>, weight, cost and back pressure of the filter

General Electric – Proposed "Retrofittable Diesel Particulate Filter (DPF) for Main Line Locomotives"

- 6-8-05 Proposed CARB ICAT project \$534K total, \$250K CARB request
- 6-28-05 ARB/Railroad MOU announced
- 7-5-05 Project withdrawn cost increased > \$600K
- 7-8-05 Supplemental funding declined

Agreement to Evaluate Others, Medium-Term and Longer-Term Alternatives

2005 MOU

- Participating Railroads will propose a spending plan (≥\$3.5 million)
- Approval of the Plan will be the discretion of the Executive Officer No timeline specified

AQMD Recommendation

Participating Railroads will provide the fund (≥\$3.5 million) to ARB for Advanced Locomotive Technology Demonstration focused on

- DPF
- SCR
- Administrated through ARB's Innovative Clean Air Technologies (ICAT) Program
- Timeline consistent with and supportive to EPA's Rulemaking process (Tier III)